



Description

Rotel's RSX-1560 receiver delivers top-of-the-line performance and all of the features you have come to expect from our premium brand. At 7 x 100 watts into 8 ohms, or 7 x 200 watts into 4 ohms, this advanced surround receiver can fill your family or media room with the most dynamic, pulse-pounding, sound effects. Yet, it is just as adept at providing all of the most delicate nuances from voice tracks and music. The RSX-1560 surround receiver features an audiophile quality Class D amplifier design, along with HDMI 1.3 connections and the ability to decode Dolby TrueHD, Dolby Digital Plus, dts-HD Master Audio and dts HD Hi-Resolution audio codecs. The RSX-1060 is a true theater command center and can also provide a multiroom audio solution with up to three additional audio zones throughout the home. All 15 series components are available in silver or black finishes.

**Note – all Rotel 15 series components may be rack mounted and remotely controlled via RS-232, IR, or 12 volt (depending on model) for complete stealth operation.*

Specifications

Power Output all channels driven	100 watts x 7/ch (20-20kHz, <0.03% THD, 8 ohms) 200 watts x 7/ch (20-20kHz, <0.03% THD, 4 ohms)	Signal / Noise Ratio (at 65 dBf)	70 dBf
IM Distortion	<0.05%	Harmonic Distortion (at 65 dBf)	0.03%
Analogue Bypass	95 dB	Stereo Separation (1 kHz)	45 dB
Digital Input	92 dB	Output Level	1 V
Input Sens. / Impedance	Line Level : 200 mV/100K ohms	Antenna Input	75 ohms unbalanced
Contour (LF/HF)	+/- 6 dB at 50 Hz / 15 kHz	AM Tuner	
Preamp Output Levels	1.0V / 1K ohm	Sensitivity	500 uV/m
Decodable Digital Input Signal	Dolby Digital, Dolby Digital EX, Dolby Prologic IIx, DTS, DTS_ES, DTS96/24, LPCM (up to 192K), Dolby TrueHD and DTS HD Mster Audio	Signal to Noise Ratio	40 dB
Video		Output Level	500 mV
Frequency Response	3 Hz - 10 MHz, +/-3 dB (Composite, S-Video) 3 Hz - 100 MHz, +/- 3 dB (Component Video)	Antenna Input	Loop Antenna
S/N Ratio	45 dB	Power Consumption (Rating)	500 watts
Input Impedance	75 ohm	Power Consumption (Idling)	79 watts
Output Impedance	75 ohm	Power Consumption (Standby)	3 watts
Output Level	1.0 Volt	Power Requirements USA	120 volts, 60 Hz
FM Tuner		Power Requirements CE	230 volts, 50 Hz
Usable Sensitivity	14.2 dBf	Dimensions (W x H x D) mm	431 x 188 x 422 mm
		Dimensions (W x H x D) in.	17 x 7 3/8 x 16 5/8 in.
		Weight (net)	15.5 Kg / 38 lbs.
		Front Panel Height	4U / 177 mm / 7 in.

www.rotel.com

The Rotel Co. Ltd.
10-10 Shinsen-Cho
Shibuya-Ku,
Tokyo 150, Japan

Rotel of America
54 Concord St.
N. Reading, MA 01864
USA
T +1 978 664 3820
F +1 978 664 4109

Rotel Europe
Dale Road
Worthing
West Sussex BN11 2BH, UK
T +44 (0) 1903 221 763
F +44 (0) 1903 221 525